



# Martini dECO FLEX

---

Velcro® receptive, flexible acoustic wall covering

---

A large, light blue, stylized lowercase letter 'm' graphic that spans the bottom half of the page.

CSR

### dECO Flex 10 - 12mm

- Flexible wall finish for straight and curved walls.
- Narrow range frequency absorption to reduce reverberated noise.
- Velcro® receptive surface.

### Applications

Used in high schools, primary schools and child care centres to help children learn and in offices and public spaces such as libraries to facilitate communication and the exchange of ideas.

### Decorative Finishes

dECO Velour is available in an extensive colour palette. dECO Velour is a non-woven fabric with nap and no pattern repeat.

### Environmental Benefits and Credentials



















Manufactured from thermally bonded polyester fibre with up to 80% recycled fibre content from post-consumer PET packaging such as empty drink bottles.

- GreenTag<sup>Cert</sup>™ certified
- Environmental Product Declaration (EPD) Certified in accordance with ISO 14025
- Product Health Declaration (PHD) certified
- Declare certified
- Suitable for Green Star™ projects
- No red list chemicals are present
- No ozone-depleting gases are used during the manufacturing process
- Safe, non-irritant, non-toxic, and non-allergenic
- Products are 100% recyclable
- High reuse potential



Martini's Product Stewardship Program can be viewed at [www.csrmartini.com.au](http://www.csrmartini.com.au)

## Finishes



## Acoustic Performance

<b>Frequencies</b>	125hz	250hz	500hz	1,000hz	2,000hz	4,000hz	<b>NRC</b>
<b>Direct Fix</b>	0.05	0.10	0.30	0.50	0.75	0.95	<b>0.40</b>

Tested in accordance with AS/ISO 354:2006

## Product Specifications

<b>Product</b>	Thickness (mm)	Width (m)	Roll Length (m)*
<b>dECO Flex</b>	10-12	1220	25

Tolerance in sizes: thickness +/- 2mm; width +/- 5mm.

\*Please note that due to the nature of the manufacturing process, there is a 10% over or under supply. Other roll lengths available upon request. Minimum length 7m.



## Physical Description and Properties

**Melting point:** 250°C

**Flash point:** None allocated

**Other properties:** Non-allergenic, low irritant, low flame response, resilient

**Ingredients:** Organic, long chain synthetic polymer

**Max service temp:** 110°C

**Alkalinity:** pH 7.8 (pH 7 is neutral)

**Moisture absorption:** Exposure to an atmosphere of 50°C and 95% RH for four days gives moisture absorption of less than 0.2% by volume

**Fire resistance:** Tested to AS ISO 9705 Corner Burn in accordance with AS 5637.1

**Group 1**  
SMOGRA not  
more than  
 $100\text{m}^2/\text{s}^2 \times 1000$

# csrmartini.com.au

---

CSR Martini Pty Limited  
P.O. Box 560, Ingleburn NSW 1890  
martinienquiries@csr.com.au  
1300 767 776

---

04/21



Disclaimer: The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Martini. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the CSR Martini website for the latest version of this document. The purchaser should independently determine the suitability of the product for the intended use and application.